



* VI LED lamps cannot be used with Frosted Globes.

Product Number	LED Spacing: P (mm)	LED Qty/run (max length)	Weight
EXBK-300-VI-__-G45_	300mm±5	2 to 120 pcs (36m)	Approx. 270g/m
EXBK-500-VI-__-G45_	500mm±5	2 to 100 pcs (50m)	Approx. 210g/m

Specifications

- Voltage : 24VAC	- Globe Style & Color:
- Wattage : 1.4W / LED	G45C: Clear
- LED Color: VI-WW : 2400K	
VI-27K: 2700K	
VI-30K: 3000K	
- IP rating: IP65 (outdoor use)	

6				Date 日付	2014/9/26	Scale 縮尺	1:2	Title	Exhibitor LED
5	End Cap	PVC						名称	(Virtual Incandescent Lamp & G45 Globe)
4	Cable	PVC	AWG12 Black	Draft 製図	Y. Terabe	Weight 重量	—	Product No.	EXBK-__-VI-__-G45_
3	Socket	PBT				Unit 単位	mm	製品番号	LED Spacing LED Color Globe Style & Color
2	Globe	PC	Globe Style: G45	Check 検図	T. Shimamura	Size 用紙	A4		
1	LED Light Source		VI (Virtual Incandescent) Lamp	Approve 承認	C. Ishibiki				
No.	Parts 部品	Material 材料	Memo 備考						



TOKI CORPORATION
トキ・コーポレーション株式会社