



* VI LED lamps cannot be used with Frosted Globes.

Product Number	LED Spacing: P (mm)	LED Qty/run (max length)	Weight
EXBK-300-VI-__-S45_	300mm±5	2 to 120 pcs (36m)	Approx. 270g/m
EXBK-500-VI-__-S45_	500mm±5	2 to 100 pcs (50m)	Approx. 210g/m

Specifications

- Voltage : 24VAC	- Globe Style & Color:
- Wattage : 1.4W / LED	S45C: Clear
- LED Color: VI-WW : 2400K	
VI-27K: 2700K	
VI-30K: 3000K	
- IP rating: IP65 (outdoor use)	

6			
5	End Cap	PVC	
4	Cable	PVC	AWG12 Black
3	Socket	PBT	
2	Globe	PC	Globe Style: S45
1	LED Light Source		VI (Virtual Incandescent) Lamp
No.	Parts 部品	Material 材料	Memo 備考

Date 日付 2014/9/26

Draft 製図 Y. Terabe

Check 検図 T. Shimamura

Approve 承認 C. Ishibiki

Scale 縮尺 1:2

Weight 重量 —

Unit 単位 mm

Size 用紙 A4

Title Exhibitor LED
名称 (Virtual Incandescent Lamp & S45 Globe)

Product No. EXBK-__-VI-__-S45_
製品番号 LED Spacing LED Color Globe Style & Color

TOKI CORPORATION
トキ・コーポレーション株式会社