




Specifications	
Current	: 700mA
Power	: 2.1W/LED
LED Spacing	: 60mm, 75mm, 100mm
Number of LEDs	: 4 to 18 LEDs
Color temperature	: 2700K, 3000K, 3500K, 4000K
Beam angle	: SP (Spread/40° x 15°), 15D(15°)
CRI	: 85

- * Do not work on live wires.
- * Dedicated constant current LED power supply is required.

P/N configuration : GRHB- - K-
LED spacing Color temp. Beam angle




6	Fixed bracket	SUS	P/N : GRHB-FIXB_ (optional parts) Qty./set
5	Lead cable		AWG18×2 [RED + , BLACK -]
4	End plate	PC	Black
3	Cover	AL	Surface treatment: Black almite
2	Extrusion	AL	Surface treatment: Black almite
1	LED lens cover		
No.	部品 Parts	材料 Material	備考 Memo

Date 日付 2016. 6. 8

Draft 製図 Hirai

Check 検図 Miwa

Approve 承認 Ichibiki



Scale 縮尺 1:1

Weight 重量 xxkg/()

Unit 単位 mm

Size 用紙 A3

Title Gradient HB with Fixed Bracket

名称

Product No. GRHB- - K- (GRHB-FIXB_)

製品番号

