




Specifications

Current	: 700mA
Power	: 2.1W/LED
LED Spacing	: 60mm, 75mm, 100mm
Number of LEDs	: 4 to 18 LEDs
Color temperature	: 2700K, 3000K, 3500K, 4000K
Beam angle	: SP(Spread/40° x 15°), 15D(15°)
CRI	: 85

* Do not work on live wires.
* Dedicated constant current LED power supply is required.

P/N configuration : GRHB- - K-
LED spacing Color temp. Beam angle



7	Parallel louver	PC	Black Cut-off angle (Side) : 50° Cut-off angle (Back) : 55° P/N : GRHB-PLVR (optional parts)
6	Fixed bracket	SUS	P/N : GRHB-FIXB (optional parts) Qty./set
5	Lead cable		AWG18×2 [RED + , BLACK -]
4	End plate	PC	Black
3	Cover	AL	Surface treatment: Black almite
2	Extrusion	AL	Surface treatment: Black almite
1	LED lens cover		
No.	部品 Parts	材料 Material	備考 Memo

Date 日付 2016. 6. 8
Draft 製図 Hirai
Check 検図 Miwa
Approve 承認 Ichibiki

Scale 縮尺 1:1
Weight 重量 xxkg/ ()
Unit 単位 mm
Size 用紙 A3

Title 名称 Gradient HB with Fixed Bracket & Parallel Louver
Product No. GRHB- - K- (GRHB-FIXB_ & GRHB-PLVR)
製品番号
TOKI CORPORATION
トキ・コーポレーション株式会社