

Specifications	
Current	: 700mA
Power	: 2.1W/LED
LED Spacing	: 60mm, 75mm, 100mm
Number of LEDs	: 4 to 18 LEDs
Color temperature	: 2700K, 3000K, 3500K, 4000K
Beam angle	: SP (Spread/40° x 15°), 15D (15°)
CRI	: 85




- * Do not work on live wires.
- * Dedicated constant current LED power supply is required.

P/N configuration : GRHB- - K-


LED spacing

Color temp.


Beam angle




Adjustable bracket
(Vertical mounting)



Swing angle and dimentions
(Vertical mounting)



Adjustable bracket
(Horizontal mounting)



Swing angle and dimentions
(Horizontal mounting)

6	Adjustable bracket	SUS	P/N : GRHB-ADJB_ (optional parts) Qty./set
5	Lead cable		AWG18×2 [RED + , BLACK -]
4	End plate	PC	Black
3	Cover	AL	Surface treatment: Black almite
2	Extrusion	AL	Surface treatment: Black almite
1	LED lens cover		
No.	部品 Parts	材料 Material	備考 Memo

Date 日付2016. 6. 8

Draft 製図Hirai

Check 検図Miwa

Approve 承認Ichibiki

Scale 縮尺1:2

Weight 重量xxkg/()

Unit 単位mm

Size 用紙A3

Title Gradient HB with Adjustable Bracket
名称

Product No. GRHB-_-K- (GRHB-ADJB_)
製品番号

TOKI CORPORATION

トキ・コーポレーション株式会社