





Specifications	
Current	: 700mA
Power	: 2.1W/LED
LED Spacing	: 60mm, 75mm, 100mm
Number of LEDs	: 4 to 18 LEDs
Color temperature	: 2700K, 3000K, 3500K, 4000K
Beam angle	: SP (Spread/40° x 15° ), 15D(15° )
CRI	: 85

\* Do not work on live wires.  
\* Dedicated constant current LED power supply is required.

P/N configuration : GRHB- - K-  
LED spacing      Color temp.      Beam angle



7	Honeycomb louver		Cut-off angle : 50° P/N : GRHB-HLVR (optional parts)
6	Fixed bracket	SUS	P/N : GRHB-FIXB_ (optional parts) Qty./set
5	Lead cable		AWG18×2 [ RED + , BLACK - ]
4	End plate	PC	Black
3	Cover	AL	Surface treatment: Black almite
2	Extrusion	AL	Surface treatment: Black almite
1	LED lens cover		
No.	部品 Parts	材料 Material	備考 Memo

Date 日付	2016. 6. 8	Scale 縮尺	1:1	<b>Title</b> Gradient HB with Fixed Bracket & Honeycomb Louver <b>Product No.</b> GRHB-_-K- (GRHB-FIXB_ & GRHB-HLVR) <b>製品番号</b>  <b>TOKI CORPORATION</b> トキ・コーポレーション株式会社
Draft 製図	Hirai	Weight 重量	xxkg/( )	
Check 検図	Miwa	Unit 単位	mm	
Approve 承認	Ichibiki	Size 用紙	A3	