




Specifications	
Current	: 700mA
Power	: 2.1W/LED
LED Spacing	: 60mm, 75mm, 100mm
Number of LEDs	: 4 to 18 LEDs
Color temperature	: 2700K, 3000K, 3500K, 4000K
Beam angle	: SP (Spread/40° x 15°), 15D(15°)
CRI	: 85


* Do not work on live wires.
* Dedicated constant current LED power supply is required.

P/N configuration : GRHB- - K-
LED spacing Color temp. Beam angle




6	Fixed bracket	SUS	P/N : GRHB-FIXB_ (optional parts) Qty. /set
5	Lead cable		AWG18×2 [RED + , BLACK -]
4	End plate	PC	Black
3	Cover	AL	Surface treatment: Black almite
2	Extrusion	AL	Surface treatment: Black almite
1	LED lens cover		
No.	部品 Parts	材料 Material	備考 Memo

Date 日付	2016. 6. 8	Scale 縮尺	1:1
Draft 製図	Hirai	Weight 重量	xxkg/ ()
Check 検図	Miwa	Unit 単位	mm
Approve 承認	Ichibiki	Size 用紙	A3



Title Gradient HB with Fixed Bracket
名称

Product No. GRHB- - K- (GRHB-FIXB_)
製品番号

 TOKI CORPORATION
トキ・コーポレーション株式会社