



L: Length	S: Distance from channel center to both bracket centers
300 ~ 799mm	125mm
800 ~ 1499mm	250mm
1500 ~ 1999mm	500mm
2000 ~ 2200mm	600mm

Specifications	
- Voltage	: 24VAC
- Power	: 1.8W/LED
- LED Color	: 24K (2400K)
	: 27K (2700K)
	: 30K (3000K)
	: 42K (4200K)
	: 50K (5000K)
- Beam Angle	: SP (Spread)
- IP rating	: IP66 (outdoor use)

Product number	LED spacing	Power consumption	LED Q'ty/run	Weight
RWCX02P-50-K-SP-L	50 ± 2mm	36 W/m	6~44 LEDs	1800 g/m

No.	Parts 部品	Material 材料	Memo 備考
8	Heat shrink tubing		
7	Lead cable	PVC	AWG14 × 2C
6	L-shaped fin	AL	Black
5	Louver	AL	Black
4	End plate	SUS	Black
3	Adjustable bracket	SUS	Sold separately. Suitable screws (dia. 4-5mm) required.
2	Channel	AL	Black
1	Body		Reveler, Beam angle: SP

Date 日付 2022/7/1

Draft 製図 Y. Terabe

Check 検図 T. Inaba

Approve 承認 C. Ishibiki

Scale 縮尺 1:3

Weight 重量 —

Unit 単位 mm

Size 用紙 A4

Title REVELER CX WITH PARTITION-GUARD
WITH ADJUSTABLE BRACKETProduct No. RWCX02P-50-K-SP-L + RWCX-ADJB2-OP
製品番号 LED Color

TOKI CORPORATION
トキ・コーポレーション株式会社