




This illustration is  
Beam angle:SP



The distance between the fixture and the illuminated surface should be 100mm or more.

There is a risk of discoloration or deterioration of the irradiated object.



| L: Length   | S: Distance from channel center to both bracket centers |
|-------------|---|
| 300~ 799mm  | 125mm   |
| 800~1499mm  | 250mm   |
| 1500~1999mm | 500mm   |
| 2000~2250mm | 600mm   |

| Specifications |                     |
|----------------|---------------------|
| Voltage        | : 24VAC             |
| Power          | : 1.8W/LED          |
| LED Color      | : 24K : 2400K       |
|                | : 27K : 2700K       |
|                | : 30K : 3000K       |
|                | : 42K : 4200K       |
|                | : 50K : 5000K       |
| Beam Angle     | : SP : Spread       |
| IP rating      | : IP66(outdoor use) |

| Product number     | LED spacing | M      | Power consumption | LED Q'ty/run | Weight   |
|--------------------|-------------|--------|-------------------|--------------|----------|
| RWCX02P-75_K-SP-L  | 75 ± 3mm    | (37.5) | 24 W/m            | 4~30 LEDs    | 1650 g/m |
| RWCX02P-100_K-SP-L | 100 ± 4mm   | (50)   | 18 W/m            | 3~22 LEDs    | 1500 g/m |

| No. | Parts 部品           | Material 材料 | Memo 備考   |
|-----|--------------------|-------------|---|
| 8   | Heat shrink tubing |             |   |
| 7   | Lead cable         | PVC         | AWG14×2C  |
| 6   | L-shaped fin       | AL          | Black   |
| 5   | Louver             | AL          | Black   |
| 4   | End plate          | SUS         | Black   |
| 3   | Adjustable bracket | SUS         | Sold separately.<br>Suitable screws(dia.4-5mm)required. |
| 2   | Channel            | AL          | Black   |
| 1   | Body               |             | Reveler, Beam angle:SP                                  |

Date 日付 2022/7/1

Draft 製図 Y. Terabe

Check 検図 T. Inaba

Approve 承認 C. Ishibiki

Scale 縮尺 1:3

Weight 重量

Unit 単位 mm

Size 用紙 A4

Title REVELER CX WITH PARTITION-GUARD  
WITH ADJUSTABLE BRACKET

Product No. RWCX02P- - K-SP-L + RWCX-ADJB2-OP  
製品番号 LED Spacing LED Color

**TOKI CORPORATION**  
トキ・コーポレーション株式会社