


The distance between the fixture and the illuminated surface should be 100mm or more.

There is a risk of discoloration or deterioration of the irradiated object.



L: Length	S: Distance from channel center to both bracket centers
300~ 799mm	125mm
800~1499mm	250mm
1500~1999mm	500mm
2000~2200mm	600mm

Specifications	
Voltage	: 24VAC
Power	: 1.8W/LED
LED Color	: 24K : 2400K
	: 27K : 2700K
	: 30K : 3000K
	: 42K : 4200K
	: 50K : 5000K
Beam Angle	: SP : Spread
IP rating	: IP66(outdoor use)

Product number	LED spacing	Power consumption	LED Q'ty/run	Weight
RWCX02P-50-_K-SP-L	50 ± 2mm	36 W/m	6~44 LEDs	1800 g/m

No.	Parts 部品	Material 材料	Memo 備考
8	Heat shrink tubing		
7	Lead cable	PVC	AWG14×2C
6	L-shaped fin	AL	Black
5	Louver	AL	Black
4	End plate	SUS	Black
3	Adjustable bracket	SUS	Sold separately. Suitable screws(dia.4-5mm)required.
2	Channel	AL	Black
1	Body		Reveler, Beam angle:SP

Date 日付 2022/7/1

Draft 製図 Y. Terabe

Check 検図 T. Inaba

Approve 承認 C. Ishibiki

Scale 縮尺 1:3

Weight 重量 —

Unit 単位 mm

Size 用紙 A4

Title 名称 REVELER CX WITH PARTITION-GUARD
WITH ADJUSTABLE BRACKET

Product No. RWCX02P-50-_K-SP-L + RWCX-ADJB2-OP
製品番号 LED Color

TOKI CORPORATION
トキ・コーポレーション株式会社