



The distance between the fixture and the illuminated surface should be 100mm or more.
There is a risk of discoloration or deterioration of the irradiated object.

Product number	LED spacing	Power consumption	LED Q'ty/run	Weight
RW-50-_K-SP	50 ± 2	36W/m	2~176 LEDs	630g/m
RW-75-_K-SP	75 ± 3	24W/m	2~176 LEDs	460g/m
RW-100-_K-SP	100 ± 4	18W/m	2~176 LEDs	370g/m

Specifications	
Voltage	: 24VAC
Power	: 1.8W/LED
LED Color	: 24K:2400K : 27K:2700K : 30K:3000K : 42K:4200K : 50K:5000K
Beam Angle	: W : Wide : SP: Spread
IP rating	: IP66 (outdoor use)

6			
5	Heat shrink tubing		
4	Lead cable		AWG14×2 Black
3	End cap	PVC	Black
2	Module		Aluminum die-cast, PBT Black
1	LED lens	PC	Beam angle:SP/Not replaceable
No.	Parts 部品	Material 材料	Memo 備考

Date 日付 2015/4/28

Draft 製図 K. Ashikaga

Check 検図 T. Shimamura

Approve 承認 C. Ishibiki

Scale 縮尺 1:2

Weight 重量

Unit 単位 mm

Size 用紙 A4

Title
名称

REVELER SP

Product No.
製品番号

RW- - K-SP

LED Spacing LED Color Beam Angle



TOKI CORPORATION
トキ・コーポレーション株式会社