



Product number	LED spacing	Power consumption	LED Q'ty/run	Weight
RW-50_K-W	50 ± 2	36W/m	2~176 LEDs	630g/m
RW-75_K-W	75 ± 3	24W/m	2~176 LEDs	460g/m
RW-100_K-W	100 ± 4	18W/m	2~176 LEDs	370g/m

Specifications	
- Voltage	: 24VAC
- Power	: 1.8W/LED
- LED Color	: 2400K
	: 2700K
	: 3000K
	: 4200K
	: 5000K
- Beam Angle	: Wide
- IP rating	: IP66

6			
5	Heat shrink tubing		
4	Lead cable		AWG14×2 Black
3	End cap	PVC	Black
2	Module		Aluminum die-cast, PBT Black
1	LED lens	PC	Beam angle:W/Not replaceable
No.	Parts 部品	Material 材料	Memo 備考

Date 日付 2015/4/28  
Draft 製図 K. Ashikaga  
Check 検図 T. Shimamura  
Approve 承認 C. Ishibiki

Scale 縮尺 1:2  
Weight 重量  $\frac{1}{2}$   
Unit 単位 mm  
Size 用紙 A4

Title 名称 REVELER  
Product No. 製品番号 RW- - K-W  
LED Spacing LED Color Beam Angle  
TOKI CORPORATION  
トキ・コーポレーション株式会社