



Specifications	
- Voltage	: 24VAC
- Power	: 1.8W/LED
- LED Color	: 2400K
	: 2700K
	: 3000K
	: 4200K
	: 5000K
- Beam Angle	: Spread
- IP rating	: IP66

Product number	LED spacing	Power consumption	LED Q'ty/run	Weight
RW-50-_K-SP	50 ± 2	36W/m	2~176 LEDs	630g/m
RW-75-_K-SP	75 ± 3	24W/m	2~176 LEDs	460g/m
RW-100-_K-SP	100 ± 4	18W/m	2~176 LEDs	370g/m

6			
5	Heat shrink tubing		
4	Lead cable		AWG14×2 Black
3	End cap	PVC	Black
2	Module		Aluminum die-cast, PBT Black
1	LED lens	PC	Beam angle:SP/Not replaceable
No.	Parts 部品	Material 材料	Memo 備考

Date 日付	2015/4/28
Draft 製図	K. Ashikaga
Check 検図	T. Shimamura
Approve 承認	C. Ishibiki

Scale 縮尺	1:2
Weight 重量	
Unit 単位	mm
Size 用紙	A4

Title 名称	REVELER
Product No. 製品番号	RW- - K-SP LED Spacing LED Color Beam Angle
TOKI CORPORATION トキ・コーポレーション株式会社	