



## Specifications

- Voltage : 24VAC
- Power : 1.8W/LED
- LED Color : 2400K  
: 2700K  
: 3000K  
: 4200K  
: 5000K
- Beam Angle : Spread
- IP rating : IP66

Product number	LED spacing	M	Power consumption	LED Q'ty/run	Weight
RW-50-K-SP	50 ± 2	(30)	36W/m	2~176 LEDs	630g/m
RW-75-K-SP	75 ± 3	(37.5)	24W/m	2~176 LEDs	460g/m
RW-100-K-SP	100 ± 4	(50)	18W/m	2~176 LEDs	370g/m

6			
5	Heat shrink tubing		
4	Lead cable		AWG14×2 Black
3	End cap	PVC	Black
2	Module		Aluminum die-cast, PBT Black
1	LED lens	PC	Beam angle:SP/Not replaceable
No.	Parts 部品	Material 材料	Memo 備考

Date 日付 2015/4/28

Draft 製図 K. Ashikaga

Check 検図 T. Shimamura

Approve 承認 C. Ishibiki

Scale 縮尺 1:2

Weight 重量

Unit 単位 mm

Size 用紙 A4

Title

名称

REVELER

Product No.  
製品番号

RW- - K-SP

LED Spacing LED Color Beam Angle

TOKI CORPORATION  
トキ・コーポレーション株式会社