2024/3/18 Rev.1	2023/12/4 TSC-0291



*For indoor use only.

Specifications	
- Voltage:	24VDC
- Wattage:	23.0W
- LED Color:	3000K (HC30K)
	3500K (HC35K)
	4000K (HC40K)
	5000K (HC50K)
- CRI:	95
- Lumen Value:	1952lm
- Dimming:	Dimmable with dedicated dimming system
- Tilt Angle:	60° left and right from below



Overall view:



Cutout:



Accessory: DC power cable with one-touch connector
(Not required when LPS-M-36-24 is not used)





Fixture height (H) can be specified from 150 to 500mm, in increments 10mm.

No.	Parts 部品	Material 材質	Memo 備考
10	One-Touch Connector	PC	
9	DC Power Cable	PVC	5.5mm x 2.1mm
8	Wire	PVC	AWG22 105。,Heat Resistant
7	Nut	Iron	M12×1.25 Trivalent Chromate
6	Flat Washer	Iron	M12, Trivalent Chromate
5	Bolt	Brass	Chrome Plated
4	Stem	Iron	Chrome Plated
3	End Cap	Brass	Chrome Plated
2	Chrome Plated	PC	Diffusion material contained
1	Body	Aluminum	Chrome Plated

Date 日付	2023/5/17	Scale 縮尺	1:2
Draft 製図	Terabe	Weight 重量	***g
Check 検図	Ashikaga	Unit 単位	mm
Approve 承認	Inaba	Size 用紙	A3

Title 名称: Micro Display Barlight

Product No. 製品番号: MDB01-HC__K-C-L1200
LED Color

TOKI CORPORATION
トキ・コーポレーション株式会社