2024/3/29 Rev.1	2023/12/4 TSC-0292



*For indoor use only.

Specifications
- Voltage: 24VDC
- Wattage: 25.9W
- LED Color: 3000K (HC30K)
3500K (HC35K)
4000K (HC40K)
5000K (HC50K)
- CRI: 95
- Lumen Value:2196lm
- Dimming:
Dimmable with dedicated dimming system
- Tilt Angle: 60° left and right from below



Overall view:



Cutout:



Accessory: DC power cable with one-touch connector
(Not required when LPS-M-36-24 is not used)





Fixture height (H) can be specified from 150 to 500mm, in increments 10mm.

No.	Parts 部品	Material 材料	Memo 備考
11	One-Touch Connector	PC	
10	DC Power Cable	PVC	5.5mm x 2.1mm
9	Wire	PVC	AWG22 105°,Heat Resistant
8	Nut	Iron	M12×1.25 Trivalent Chromate
7	Flat Washer	Iron	M12, Trivalent Chromate
6	Bolt	Brass	Chrome Plated
5	Stem	Iron	Chrome Plated
4	Center Cap	Brass	Chrome Plated
3	End Cap	Brass	Chrome Plated
2	Chrome Plated	PC	Diffusion material contained
1	Body	Aluminum	Chrome Plated

Date 日付	2023/5/17	Scale 縮尺	1:2
Draft 製図	Terabe	Weight 重量	***g
Check 検図	Ashikaga	Unit 単位	mm
Approve 承認	Inaba	Size 用紙	A3

Title 名称: Micro Display Barlight

Product No. 製品番号: MDB01-HC__K-C-L1500 (LED Color)

TOKI CORPORATION
トキ・コーポレーション株式会社